





Door/Window Sensor

Securifi AL-DSW04 Micro Door / Window Sensor


Instant Alerts




Peace of Mind



Security



Automation



Product Description

| | |
|--|---|
| Compatible with ZigBee Products | Easy, Low-Cost Installation with Adhesive Tapes or Screws |
| Small, Modest Design for Any Location | Built-in Tamper Switch for Additional protection |
| Up to 3-Year Battery Life with One Replaceable Lithium CR2032 | Radio Frequency: 2.4GHz |
| RF Communication Range: 300M (Open Air) | ZigBee Channel: 11, 14, 15, 19, 20, 24, 25 |
| Switch: Tamper Switch / Reset x 1 | LED Indicator: Green LED x 1 |
| RF Supervision Interval: 24 Mins | Battery: CR2032 x 1 |
| Average Battery Life: 3 Years (20 triggers/day) | Adjustable Sensitivity Interval 4 - 10m |
| ZigBee Profile: HA1.2, ZigBee: Built-in Ember ZigBee Module | Temperature Sensor Accuracy : +/- 2 degree |
| Dimensions (H x W x L) Main Unit : 7.4mm x 26mm x 51mm (0.29" x 1.02" x 2") | Dimensions (H x W x L) Magnet Unit : 7.4mm x 15.5mm x 28.3mm (0.29" x 0.61" x 1.11") |
| Compliance: FCC, ETL (UL634) | Operation Temperature: 0° - 40°C (32° - 104°F); Humidity: 10% - 80% RH (non-condensing) |
| Ordering Information: SZ-DWS04: ZigBee Micro Door / Window Sensor | Storage Temperature: -20° - 60°C (-4° - 140°F); Humidity: -20% - 60% RH (non-condensing) |



Securifi Ltd.
+886-2-2726-0100
sales@securifi.com
<http://www.securifi.com>